

HUBBELL



HBL504SS

Preso da banchina in acciaio inossidabile resistente UV stagna quando chiusa. Fori di montaggio a 60,3 mm dal centro. Diametro posteriore 55 mm. Cappuccio di protezione posteriore.

Stainless steel shore power inlet has a gasketed, self-closing cover. Watertight when cover is screwed in place. Mounting holes are 60,3 mm on centers and the rear portion has a 55 mm diameter.



HBL63CM64

Spina 50A in ottone nichelato. Compatibile con prese 504.

Nickel plated brass connector body has a heat resistant thermo set interior and combination metal and rubber cord grip.



HBL77CM15

Cappuccio di protezione per spine 63CM64. La ghiera metallica rende la connessione stagna.

Yellow Seal-Tite® cover for connector bodies when used with shore power inlets. Threaded metallic sealing rings makes connection watertight.



HBLPHTVSS

Preso in acciaio inox AISI 316 con attacchi telefono e TV. La presa è completamente stagna quando chiusa. Fori di montaggio 60,3 mm dal centro. Diametro posteriore 55 mm.

Stainless steel inlet provides telephone and a cable TV connections in one unit. It has a gasketed, self-closing cover. Watertight when cover is screwed in place. Mounting holes are 60,3 mm on centers and the rear portion has a 55 mm diameter.



PH6624

Spina nera femmina per telefono.

Black locking type connector body used on telephone cable sets adapter.



PH7440

Cappuccio di protezione stagno. Giallo per spina PH6624.

Yellow Seal-Tite® cover for waterproofing PH6624. Connector body on cable sets when connecting to an inlet.



CODICE	HUBBEL	Descrizione - Description			
Code	Code	Amp	Volt		
1101000	HBL504SS	50	125-250	presa fissa stagna	watertight power inlet
1101100	HBL63CM64	50	125-250	spina volante	connector body
1101200	HBL77CM15	50	125-250	cappuccio protezione	protection cover
1101500	HBLPHTVSS	ph-tv		presa fissa	ph and tv power inlet
1101600	PH6624	ph-tv		spina volante	connector body
1101700	PH7440	ph-tv		cappuccio protezione	protection cover